

# IMC TLA Report

## Performance Plot

TLA: 930320 ElecDesc: IDBP63-1090-20-40-S12-Z-Z-T20-N2

Marker	MHz	Spec dB	dBa	dBc	VSWR	RL	Phase	Delay (ns)
1	1015.0	80.00	75.04	73.89		0.01		
1 Tempcomp	1015.6		74.73	73.58		0.01		
2	1050.0	50.00	51.03	49.88		0.05		
2 Tempcomp	1050.6		50.45	49.30		0.05		
4 Tempcomp	1079.3		1.91	0.76	1.36	16.26		71.09
4 PB Low	1080.0	2.50	1.61	0.46	1.18	21.77	137.79	66.54
5 Fo	1090.0	2.50	1.15	0.00	1.44	14.86	62.33	38.47
6 PB High	1100.0	2.50	1.66	0.51	1.20	20.79	96.55	57.27
6 Tempcomp	1100.6		1.97	0.82	1.46	14.64		62.17
8 Tempcomp	1129.3		47.31	46.16		0.05		
8	1130.0	50.00	47.91	46.76		0.05		
9 Tempcomp	1164.2		68.41	67.26		0.02		
9	1165.0	80.00	68.76	67.61		0.02		
PB Variation		1.00		0.82				

